

Ampliroll®

50,000 POUNDS

160 SERIES



Why buy a HookLift?

Do you have trucks that are not always being used?
Do you have a difficult time finding quality drivers?
Is there a piece of equipment you could use, but
can't justify adding another truck?

**It's Multi-tasking for your truck.
The possibilities are Infinite.**

With an Ampliroll® you can do just about anything.

Deliver — Load — Dump



FEATURES

- **Sliding Jib** gives you greater range of body lengths and optimal weight distribution.
- **Twin Pivot** allows you to dump a uniform pile of material.
- **Dual Cylinders** gives greater stability while dumping and loading.
- **Safely** operated from the drivers seat.
- **Dock Level** loading and unloading.
- **Double** your payload by pulling another body on a trailer.
- **Maneuverable** to operate, the container can be loaded within a 60 degree arc.
- **Spot** the container exactly where you want it, by pushing it into place with no damage.
- **Quickly** loads a body in less than one minute.
- **Investment** that will outlast your truck, Amplirolls® will last over **25 years**.
- Meets all highway safety standards.



The Ampliroll® HookLift was invented in 1969. Our process of laser cutting and robotic welding enables us to provide you with a complete line of hooklifts, that eliminate the use of **SHIMS** and **WEAR PADS**.

***Ampliroll® has been imitated
but never duplicated.***

Compare the difference before you buy.



| Ampliroll® Model | AMP 160-212-20 | AMP 160-232-22 |
|---|-------------------|-------------------|
| Previous Model | AL 160/1700-20 | AL 160/1900-22 |
| Lifting Capacity (including container) | 50,000 lbs. | 50,000 lbs. |
| Shipping Weight | 5565 lbs. | 5730 lbs. |
| Dump Angle | 51 degrees | 56 degrees |
| Cab to Trunnion | 174 to 190 inches | 186 to 210 inches |
| Over-All Length | 220 inches | 242 inches |
| Body Length | 15 to 22 feet | 16 to 24 feet |

Hydraulic Specifications:

Pump - Axial piston, 5,700 psi, 23 GPM @ 1,200 RPM, SAE B, direct mount
 Controls - Low pressure hydraulic or air in cab
 Reservoir - 20 gallons
 Filter - 10 micron, return line with replaceable cartridge
 Maximum operating pressure - 5,000 psi
 Hoses, tubes & fittings all JIC/SAE specifications

Steel: Special Alloy **ASTM A 514** in jib, central arm and tilting frame
ASTM A 572 grade 60 type 2 subframe


Safety Devices: Safety valve prevents jib operation during dump mode
 Counter-balance valve to hold cylinder if hose breaks
 Automatic locking device for dump mode
 Slide through container locks

Truck Requirements: GVWR - 50,000 to 70,000 lbs
 Front Axle capacity - 16,000 to 20,000 lbs
 Rear Axles capacity - 40,000 to 60,000 lbs
 Minimum RBM 2,500,000 in. lbs.

Notice: Longer containers may not comply with I.C.C. bumper regulations and can effect dump angle.

Optional
 Manual Adjustable
 54" to 62"

Inside Controls



marrel
 CORPORATION

4750 14 Mile Road NE
 Rockford, MI 49341
 Phone: (616) 863-9155
 Fax: (616) 863-9177
 Toll Free: (866) 822-3580
 E-mail: equipment@amplirollusa.com
www.amplirollusa.com

Distributed by:

