

18,000
POUNDS

AL 95 Series &
AMP 95 Series



WHY BUY A HOOKLIFT?

Do you have trucks that are not
always being used?

Do you have a difficult time finding
quality drivers?

Is there a piece of equipment you
could use, but can't justify adding
another truck?

**It's Multi-tasking for your truck.
The possibilities are Infinite.**

DELIVER | LOAD | DUMP

The **Ampliroll Hooklift** was invented in 1969. Our process of laser cutting and robotic welding enables us to provide you with a complete line of hooklifts, that eliminate the use of SHIMS and WEAR PADS.



FEATURES:

- **Sliding Jib** gives you greater range of body lengths and optimal weight distribution.
- **Twin Pivot** allows you to dump a uniform pile of material.
- **Dual Cylinders** gives greater stability while dumping and loading.
- **Safely operated** from the drivers seat.
- **Dock Level** loading and unloading
- **Double your payload** by pulling another body on a trailer.
- **Maneuverable** to operate, the container can be loaded within a 60 degree arc.
- **Spot** the container exactly where you want it, by pushing it into place with no damage.
- **Quickly loads** a body in less than one minute.
- **Investment** that will outlast your truck, Amplirolls® will last over 25 years.
- **Meets** all highway safety standards.

	AL 95SS-12	AMP 95SS-12	AL 95S-15	AMP 95S-15	AL 95L-16	AMP 95L-16
LIFTING CAPACITY (including container)	18,000 lbs.					
SHIPPING WEIGHT	2408 lbs.	2408 lbs.	2408 lbs.	2408 lbs.	2417 lbs.	2408 lbs.
DUMP ANGLE	54°	58°	54°	60°	54°	60°
CAB TO AXLE*	96" - 120"	96" - 120"	120" - 138"	120" - 138"	126" - 150"	126" - 150"
OVER ALL LENGTH From Hook**	146"	146"	162"	162"	174"	174"
BODY LENGTH	10' - 13'	11' - 13'	10' - 16'	13' - 16'	11' - 17.5'	14' - 17.5'

HOOK HEIGHT

Standard

54"

Optional

36" or MA 36"-54" / TEL 36"-54"

STEEL: SPECIAL ALLOY

ASTM A 572

in jib, central arm and tilting frame

SAFETY DEVICES:

Safety valve

prevents jib operation during dump mode

Counter-balance valve

to hold cylinder if hose breaks

Automatic locking device

for dump mode

Slide through container locks

HYDRAULIC SPECIFICATIONS:

Pump

Axial piston, 5,7000 psi, 11 GPM @1,200 RPM,-
Standard - DIN Shaft or Optional SAE 7/8th Shaft

Controls

cable operated valve

Reservoir

12 gallons

Filter

10 micron, return line with replaceable cartridge

Maximum operating pressure

4,200 psi

Hoses, tubes & fittings

all JIC/SAE specifications

TRUCK REQUIREMENTS:

GVWR

19,500 to 26,000 lbs

Front Axle Capacity

6,000 to 8,000 lbs

Rear Axles Capacity

15,000 to 18,000 lbs

NOTICE:

Longer containers may not comply with I.C.C. bumper regulations and can effect dump angle.

*Need to confirm CA or CT with factory or local dealer for proper installation.

**Some subframes are longer, check with local dealer.

Distributed by:



CORPORATION

4750 14 Mile Road NE | Rockford, MI 49341
Phone: 616-863-9155
Fax: 616-863-9177
Toll Free: 866-822-3580
equipment@amplirollusa.com
amplirollusa.com