

AMPLIROLL® USA offers a comprehensive selection of truck-mounted accessories and roll-on/off bodies that we can package with our hooklifts*, providing you a single-source acquisition.

- Accessories include:
- Aerial lifts
 - Cranes
 - Grapple systems, and more

- Choose from a variety of interchangeable bodies:
- Cement mixers
 - Dump bodies
 - Flatbeds
 - Septic pumpers
 - Waste containers
 - Water tankers, and more

KEY HOOKLIFT FEATURES:

- Sliding jib for greater range of body lengths & optimal weight distribution.
- Maneuverable; to operate, the container can be loaded within a 60 degree arc.
- Dual cylinders provide greater stability while dumping and loading.
- Safely operated from the drivers seat.
- Dock-level loading and unloading.
- Precision Spotting; position container exactly were you want by pushing it into place with no damage.

Why Buy an
AMPLIROLL® Hooklift System?

When you purchase an AMPLIROLL® Hooklift System, you are buying more than just a piece of equipment. You are purchasing one of the safest, most efficient, and versatile hook loader systems on the market, full-stop!

SAFETY
AMPLIROLL® Hooklift Systems feature in-cab controls so operators can load and unload roll-offs safely from inside their vehicle, reducing the chance of bodily harm and expensive injury claims.

EFFICIENCY
Turnaround times of two minutes or less with a 30° off-center approach and drop or hook times requiring no out of cab driver assistance.

VERSATILITY
One Truck, with infinite possibilities! AMPLIROLL® USA can match one chassis with many combinations of interchangeable accessories and roll-off bodies.* - Contact AMPLIROLL® USA for a customized package deal before going anywhere else - you won't be sorry!

With an AMPLIROLL® Hooklift System*, your investment will outlive your truck with an average lifespan of 25 years!

**See Capacity Chart for Hooklift Models*



MARREL
CORPORATION

4750 14 Mile Road NE | Rockford, MI 49341
Phone: 616-863-9155
Fax: 616-863-9177
Toll Free: 866-822-3580
equipment@amplirollusa.com
amplirollusa.com

LIFTING CAPACITY	MODEL	SHIPPING WEIGHT	DUMP ANGLE	CAB TO AXLE*	LENGTH FROM HOOK	BODY LENGTH	HOOK HEIGHT (Standard/Optional)
13,000 lbs	AL 90S-12	1790 lbs.	58°	84" - 108"	124"	9' - 13.5'	36" / 54" (Reduces capacity to 10,000 lbs.)
	AL 90L-14	1790 lbs.	61°	108" - 126"	144"	10' - 14'	
18,000 lbs	AL 95SS-12	2408 lbs.	54°	96" - 120"	146"	10' - 13'	54" / 36" or MA 36"-54" / TEL 36"-54"
	AMP 95SS-12	2408 lbs.	58°	96" - 120"	146"	11' - 13'	
	AL 95S-15	2408 lbs.	54°	120" - 138"	162"	10' - 16'	
	AMP 95S-15	2408 lbs.	60°	120" - 138"	162"	13' - 16'	
	AL 95L-16	2417 lbs.	54°	126" - 150"	174"	11' - 17.5'	
	AMP 95L-16	2408 lbs.	60°	126" - 150"	174"	14' - 17.5'	
20,000 lbs.	AMP 100SS-12	2408 lbs	58°	96" - 120"	144"	10' - 13'	54" / 36" or MA 36"-54" / TEL 36"-54"
	AL 100SS-12	2408 lbs	54°	96" - 120"	146"	10' - 13'	
	AMP 100S-15	2408 lbs	60°	120" - 138"	160"	11' - 16'	
	AL 100S-15	2408 lbs	54°	120" - 138"	162"	10' - 16'	
	AMP 100L-16	2417 lbs	60°	126" - 150"	172"	11' - 17.5'	
	AL 100L-16	2417 lbs	54°	126" - 150"	174"	11' - 17.5'	
26,000 lbs.	AL 120SS-10	3307 lbs.	52°	96" - 108"	127"	9' - 12'	54" / 36" or MA 36"-54" / TEL 36"-54"
	AL 120SS-12	3307 lbs.	52°	102" - 110"	137"	9' - 14'	
	AL 120S-14	3307 lbs.	53°	120" - 138"	156"	11' - 16'	
	AL 120L-16	3450 lbs.	60°	138" - 156"	178"	12' - 17.5'	
31,000 lbs.	AMP 140-183-16	4260 lbs.	58°	158" - 180"	192"	13' - 18'	61 3/4" / 54" or MA 54" - 61 3/4"
	AMP 140-189-18	4260 lbs.	58°	170" - 192"	200"	13' - 20'	
35,000 lbs.	AMP 140-165-15	4510 lbs	52°	126" - 151"	175"	12' - 18'	61 3/4" / 54" or MA 54" - 61 3/4"
	AMP 140-181-17	4510 lbs	58°	138" - 164"	190"	13' - 19'	
	AMP 140-197-18	4686 lbs.	58°	154" - 186"	206"	13' - 20'	
	AMP 140-220-20	4994 lbs.	58°	178" - 204"	230"	15' - 22'	
40,000 lbs.	AMP 150-165-15	4510 lbs.	52°	126" - 151"	177"	12' - 18'	61 3/4" / 54" or MA 54" - 61"
	AMP 150-181-17	4510 lbs.	58°	138" - 164"	190"	13' - 19'	
	AMP 150-197-18	4686 lbs.	58°	154" - 186"	206"	13' - 20'	
	AMP 150-220-20	4994 lbs.	58°	178" - 204"	230"	15' - 22'	
50,000 lbs.	AMP 160-212-20	5565 lbs.	58°	174" - 190"	222"	15' - 22'	61 3/4" / 54" or MA 54" - 61 3/4"
	AMP 160-212-20-PA	5565 lbs.	58°	174" - 190"	225"	15'- 22'	
	AMP 160-232-22	5730 lbs.	58°	186" - 210"	242"	16' - 24'	
60,000 - 65,000 lbs.	AMP 160-185-17	5148 lbs.	56°	138" - 168"	194"	12' - 19'	61 3/4"
	AL 160/2000-22	7030 lbs.	57°	186" - 200"	233"	16' - 24'	

AMPLIROLL® USA



4750 14 Mile Rd. NE
Rockford, MI 49341-8427

Website: amplirollusa.com

Toll Free: 866.822.3580
Local: 616.863.9155
Fax: 616.863.9177